



TEXAS TECH UNIVERSITY

College of Human Sciences

Department of Design

**TEXAS TECH CLUTCH SEWING PROJECT
4-H WORKSHOP
SPONSORED BY HI-TECH FASHION GROUP
2011**

Materials:

3/8 Yard of Fabric (*Suggested: Felt, Worsted Wool, Suede, Pleather)

3/8 Yard of Ribbon

1 Decorative Attachment

Pinking Shears

Glue Stick or Basting Glue

Scissors

Thread

Pins

Order of Sewing:

1. With right side of fabric facing up fold lower guideline of pleat up to meet upper guideline of the pleat.
2. Pin pleat in place.
3. Press
4. Apply glue to outer edges of ribbon on the wrong side.
5. Place purchased ribbon between guidelines and pin.
6. With wrong sides together, fold lower edge of clutch to upper fold line.
7. Sew ¼" away from the edge from the top of the clutch to the bottom avoiding the fold down flap and backstitching at beginning and end.
8. Fold down the top of the flap and tuck under the purchased ribbon to close.
9. Press the upper edge of the clutch.
10. Pin or sew purchased decorative attachment to ribbon only.

Rachel Anderson

Instructor

Apparel Design & Manufacturing

College of Human Sciences

Texas Tech University